

SPECIFICATIONS



Model

ATN120

Weight

80 lbs

Note: Dimensional tolerances are +1% due to manufacturing process.

*Intended for indoor use only

Dimensions

Bed Deck Length 77"

Bed Deck Width 29"

Height 15"

Overall Length 79"

Overall Width 31"

Recommended Mattress

29"x77"



DETAILS

Color

Pine Cone, River Rock, Lagoon, Graphite

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

ATN123: Space-Saver with no Mounting

Holes

Assembly

None required

Patents

This product may be covered by US Patent Nos. US 8,007,059 B2, and US 10,507,150 B2.

Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Anti-ligature design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

Installation

Wedge anchors and 3/8" bolts required for permanently attaching to floor. Anchors and bolts not supplied by Norix. Groove along underside edge for caulk application (caulk not supplied by Norix).

Warranty

10 year limited replacement warranty. Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Performance Test Standards

Product tested to 1,000 lbs static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture