

# Attenda®

## Space-Saver Bed



**Model** ATN150  
**Weight** 85 lbs / 38.6 kg

Dimensions	in	cm
Overall Length	80"	203.2
Overall Width	32"	81.3
Height	15"	38.1
Bed Deck Length	78"	198.1
Bed Deck Width	30"	76.2

Note: Dimensional tolerances are +1% due to manufacturing process.

### Mattress Size

30"x79" (76.2x200.7 cm)

### Finishes

See Design Guide for finish options.

### Options

- **ATN153:** No Mounting Holes

### Assembly

None required.

\*Intended for indoor use only

### Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Ligature resistant design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

### Warranty

10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.2-23.9°C) with a Relative Humidity of 35%.

### Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions. Norix recommends regular monthly inspections of all fasteners. Bolt-down fasteners should be tight with no gaps larger than 1/16" (0.2 cm) between the bottom of the bed and the floor. There should be no visible cracks in the caulk, if applied.

### Installation

Wedge anchors and 3/8" (0.95 cm) bolts required for permanently attaching to floor. Anchors and bolts not supplied by Norix. Groove along underside edge for caulk application (caulk not supplied by Norix).

### Patents

This product may be covered by US Patent Nos. US 8,007,059 B2 and US 10,507,150 B2.

### Performance Test Standards

- Product tested to 1,000 lbs (453.6 kg) static load.

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

