

SPECIFICATIONS



Model

ATN801

Weight

75-80 lbs

*Intended for indoor use only

Dimensions

Width	26"
Depth without door	24"
Depth with door	25.5"
Height	78.4"

Note: Dimensional tolerances are +1% due to manufacturing process.



DETAILS

Color

Pine Cone, River Rock, Lagoon, Graphite

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

ATN801LK, ATN801RK: Key lock or wing knob cam latch with magnetic catch

ATN801LL, ATN801RL: Right or left hinge.

ATN800: No Door

Assembly

Door field reversible

Patents

This product may be covered by US Patent No. US 8,007,059 B2.

Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

Installation

Anchors required for permanently attaching to solid wall. Anchors not supplied by Norix. Bottom and back surfaces have a channel to accommodate security caulk. (Caulk not supplied by Norix).

Warranty

10 year limited replacement warranty. Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture