Ultra-Max® Armless Chair



SPECIFICATIONS



Model	Dimensions	
C160-P	Seat Height	17.5"
Weight	Seat Width	19"
17 lbs	Overall Height	31.5"
	Depth	23"
*Intended for indoor use only	Width	19"









DETAILS

Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ganging plates, Stainless Steel Bolt-down Plate, Factory Ballasting (50 lbs)

*Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required

Fabrication & Material

One-piece, rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Anti-ligature design with no internal openings. Full perimeter floor support to facilitate ease of cleaning and to prevent concealment of contraband. Molded-in steel threaded inserts for optional ganging side-to-side or bolt-down applications. Made in the U.S.A.

Installation

Required for bolt-down plates and ganging plates.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Performance Test Standards:

- ANSI/BIFMA X5.1 2002 General Purpose Office Chairs
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items
- UL94 HB Test for Flammability of Plastic Materials