

## SPECIFICATIONS



Models	Width	Weight
C212-2	44"	81 lbs
C212-3	65"	110 lbs
C212-4	86"	145 lbs

\*Intended for indoor use only

Dimensions	
Seat Height	18"
Seat Width	17"
Seat Depth	16"
Overall Height	31.4"
Depth	25"



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Available as a free-standing unit with glides or fitted with tabs for bolt-down installation.

Alternative arm option: End Arms (See separate specification sheet)

### Assembly

None required

### Fabrication & Material

Base Frame: Tubular steel, bent and welded to provide arm or armless in-line seating. Standard configurations for 2 to 4 people. Flat steel plate welded to the frame at each seat location to provide strength, support, and a mounting platform on which the seat is attached. 2" diameter, 14 gauge steel with 11 gauge steel seat supports.

Seats: One-piece seat and back. Smooth maintenance free surface allows for easy cleaning. Molded-in threaded steel inserts provide for tamper resistant attachment to base frame. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

### Installation

For bolt-down application, fasten to floor. Floor mounting hardware included.

### Warranty

10 year limited replacement warranty

### Maintenance

Frame: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

### Performance Test Standards

- Product tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times ANSI/BIFMAX 5.4 15.4.2012 (250 lbs. from 18").

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7

### Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture