Boulder™ End Arm Beam Seating



SPECIFICATIONS



| Models | Width | Weight |
|--------|-------|---------|
| C213-3 | 65" | 118 lbs |
| C213-4 | 86" | 153 lbs |
| C213-5 | 107" | 195 lbs |

^{*}Intended for indoor use only

Dimensions

| Seat Height | 18" |
|----------------|------|
| Seat Width | 17" |
| Seat Depth | 16" |
| Overall Height | 31.4 |
| Depth | 25" |
| Arm Height | 24" |









DETAILS

Color

<u>Frame:</u> Black, Metallic Silver <u>Seat:</u> Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray, Rayen

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Available as a free-standing unit with glides or fitted with tabs for bolt-down installation.

<u>Alternative arm options:</u> No Arms or End and Divider Arms. (See separate specification sheets)

Assembly

None required

Fabrication & Material

Base Frame: Tubular steel, bent and welded to provide arm or armless in-line seating. Standard configurations for 3 to 5 people. Flat steel plate welded to the frame at each seat location to provide strength, support, and a mounting platform on which the seat is attached. 2" diameter, 14 gauge steel with 11 gauge steel seat supports.

Seats: One-piece seat and back. Smooth maintenance free surface allows for easy cleaning. Molded-in threaded steel inserts provide for tamper resistant attachment to base frame. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

Made in the U.S.A.

Installation

For bolt-down application, fasten to floor. Floor mounting hardware included.

Warranty

10 year limited replacement warranty

Maintenance

<u>Frame:</u> Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

<u>Seats</u>: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

TESTING

Performance Test Standards

- Product tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times ANSI/BIFMAX 5.4 15.4.2012 (250 lbs. from 18").

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture