

## SPECIFICATIONS



Models	Width	Weight	Dimensions	
C223-1	26"	50 lbs	Seat Height	18.5"
C223-2	50"	77 lbs	Seat Width	20"
C223-3	74"	113 lbs	Seat Depth	24.3"
C223-4	98"	149 lbs	Overall Height	34.5"
			Depth	28"
			Arm Height	26.3"

\*Intended for indoor use only



## DETAILS

### Color

**Frame:** Black, Metallic Silver

**Seat:** Canyon, Wild Berry, Meadow, Pine Cone, Lagoon, Raven

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Available as a free-standing unit with tamper-resistant, nylon-bottom leveler glides, or fitted with steel tabs for bolt-down installation.

**Alternative arm option:** End & Divider Arms (See separate specification sheets)

### Assembly

None required

### Fabrication & Material

**Base Frame:** Tubular steel, bent and welded to provide arm or armless in-line seating. Standard configurations for 1 to 4 people. Flat steel plate welded to the frame at each seat location to provide strength, support, and a mounting platform on which the seat is attached. 2" diameter, 14 gauge steel with 11 gauge steel seat supports.

**Seats:** One-piece seat and back. Smooth maintenance free surface allows for easy cleaning. Molded-in threaded steel inserts provide for tamper resistant attachment to base frame. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

### Installation

For bolt-down application, fasten to floor. Floor mounting hardware included.

### Warranty

10 year limited replacement warranty.

### Maintenance

**Frame:** Norix® recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated steel.

**Seats:** For routine and regular cleaning maintenance, Norix® recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

### Performance Test Standards

- Product tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs. from 18").

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

### Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture