

Jupiter Table

NORIX®

SPECIFICATIONS



Model	Dimensions	Weight
CY3600	(36" Diameter x 29.3"H)	68 lbs
CY3636	(36"L x 36"W x 29.3"H)	80 lbs
CY4200	(42" Diameter x 29.3"H)	82 lbs
CY4242	(42"L x 42"W x 29.3"H)	99 lbs
CY4800	(48" Diameter x 29.3"H)	103 lbs

*Intended for indoor use only



DETAILS

Color

Base: Raven

Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve and Titanium Evolve Game Top with Black edge.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ballasting available (100 lbs).

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: Slightly textured, maintenance-free surface allows for easy cleaning. Rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading).

Top: Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1/8" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" thick edge profile. Made in the U.S.A.

Installation

Ballast weighting required to validate warranty. Recommended 100 pounds of sand ballast. Not supplied by Norix.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG
- Complies with Healthier Hospitals guidelines

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items

Performance Test Standards

Product tested to 1,000 lb static load