# Element<sup>™</sup> Lounge Chair

# **SPECIFICATIONS**



# DETAILS

#### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

#### Options

Available in California TB133 compliant upholstery.

#### Upholstery

View our upholstery selections at www.norix. com/fabrics. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G,

Grade H, COM.

#### Assembly

None required

I	Dimensions		COM Yards	
	Seat Height	18″	Total Yards	7.2
t	Seat Width	23″	Seat Yards	1.4
S	Overall Height	32.5″	Back Yards	2.25
	Depth	29″	Arm Yards	3.55
ed for indoor use only	Width	29″		
	Arm Height	26.4″		

## Stinson

## **Fabrication & Material**

Frame: The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

Cushions: Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications. Arm Panel: Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

## Installation

None required

## Warranty

10 year limited replacement warranty

#### Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

# TESTING

## **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

• Compliant with Healthier Hospitals guidelines

#### **Performance Test Standards**

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

# NORIX.COM





ΕA Weight 100 lbs

Model

\*Intende