Element[™] Love Seat

NORIX

SPECIFICATIONS



Model	Dimensions		COM Yards	
EC	Seat Height	18"	Total Yards	10.85
Weight	Seat Width	46"	Seat Yards	2.8
141 lbs	Overall Height	32.5"	Back Yards	4.5
	Depth	29"	Arm Yards	3.55
*Intended for indoor use only	Width	52"		



26.4"

DETAILS —

Color

Arm Caps and Feet: Raven

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Available in California TB133 compliant upholstery

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Fabrication & Material

<u>Frame:</u> The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

Arm Height

<u>Cushions:</u> Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications.

<u>Arm Panel:</u> Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

Installation

Stinson

None required

Warranty

10 year limited replacement warranty

Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,500 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

