# Element<sup>™</sup> Love Seat

# **NORIX**

# **SPECIFICATIONS**



| Model                         | Dimensions     |       | COM Yards   |       |
|-------------------------------|----------------|-------|-------------|-------|
| EC                            | Seat Height    | 18"   | Total Yards | 10.85 |
| Weight                        | Seat Width     | 46"   | Seat Yards  | 2.8   |
| 141 lbs                       | Overall Height | 32.5" | Back Yards  | 4.5   |
|                               | Depth          | 29"   | Arm Yards   | 3.55  |
| *Intended for indoor use only | Width          | 52"   |             |       |

26.4"



Arm Height





#### **DETAILS**

# **Finishes**

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

#### **Options**

Available in California TB133 compliant upholstery

#### **Upholstery**

View our upholstery selections at <a href="www.norix.com/fabrics">www.norix.com/fabrics</a>. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

#### **Assembly**

None required

#### **Fabrication & Material**

<u>Frame:</u> The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

<u>Cushions:</u> Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications.

<u>Arm Panel:</u> Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

#### Installation

None required

#### Warranty

10 year limited replacement warranty

#### Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

#### **TESTING**

# **Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

# **Performance Test Standards**

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,500 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")