# Forma Arm Chair

# **NORIX**

#### **SPECIFICATIONS**



Model		Dimensions		COM Yards	
FA		Seat Height	18.5"	Total Yards	8.5
Weight		Overall Height	32"	Seat Yards	1.75
Plinth Base	83 lbs	Depth	30"	Back Yards	1.25
Steel Base	91 lbs	Width	29.5"	Arm Yards	5.5
		Arm Height	26"		







# **DETAILS**

#### Color

Plinth Base: Moss, Fossil & Raven

Steel Base: Metallic Silver

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### **Options**

Ganging or Bolt-down.

Factory Ballasting (Plinth Base only) (50 lbs).

\*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

#### **Upholstery**

View our upholstery selections at www.norix. com/fabrics. Fabric Grade Levels: Grade A-H and COM. Seat, arms and back are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

#### **Fabrication & Material**

\*Intended for indoor use only

Constructed of wood, 2.5" thick foam, enclosed wood panel with secure hardware and finished with upholstery. Optional plinth or steel base. Made in the U.S.A.

#### **Assembly**

None required

#### Installation

Required for Ganging plates and Bolt-down.

#### Warranty

10 year limited replacement warranty.

#### Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabric.

#### **TESTING**

# **Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

# **Performance Test Standards**

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Product tested to 750 lb static load
- Meets the requirements of ANSI/BIFMA X5.4-2012