

SPECIFICATIONS



Model		Dimensions		COM Yards	
FO		Height	32"	Total Yards	3.6
Weight		Seat Height	18.5"	Seat Yards	1.8
Plinth Base	47 lbs	Front Width	875"	Back Yards	1.8
Steel Base	50 lbs	Back Width	31.1"		

*Intended for indoor use only



DETAILS

Color

Plinth Base: Moss, Fossil, Raven

Steel Base: Metallic Silver

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ganging or Bolt-down.

Factory Ballasting (*Plinth Base only*) (50 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade A-H and COM. Seat, arms and back are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

Fabrication & Material

Constructed of wood, 2.5" thick foam, enclosed wood panel with secure hardware and finished with upholstery. Optional plinth or steel base. Made in the U.S.A.

Assembly

None required

Installation

Required for Ganging plates and Bolt-down.

Warranty

10 year limited replacement warranty.

Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabric.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Product tested to 750 lb static load
- Meets the requirements of ANSI/BIFMA X5.4-2012