

## SPECIFICATIONS

**Model**

FO

**Weight**

47.5 lbs

**Dimensions**

Height 13.5"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

**Color**

Laminate Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve with black edge.

Base: Maple, Teak, and Walnut colored finish.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Assembly**

None required

**Fabrication & Material**

Top: Decorative high pressure laminate is bonded to a core of 45 lb density particle board with embedded T-nuts for securing top to base. Polyurethane edge is radiused for safety and pressure fused to the top, rendering it firmly attached and highly sanitary. 1<sup>3</sup>/<sub>4</sub>" thick edge profile.

Base: Glued mortise and tenon. 3" solid hardwood frame with tapered legs. Made in the U.S.A.

**Installation**

None required

**Warranty**

10 year limited replacement warranty

**Maintenance**

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

## TESTING

**Performance Test Standards**

- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs. from 18")

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG
- Compliant with Healthier Hospitals guidelines

## SPECIFICATIONS

**Model**

FO

**Weight**

44.5 lbs

**Dimensions**

Height 12.2"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

**Color**

Laminate Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve with black edge.

Base: Metallic Silver

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Assembly**

None required

**Fabrication & Material**

Top: Decorative high pressure laminate is bonded to a core of 45 lb density particle board with embedded T-nuts for securing top to base. Polyurethane edge is radiused for safety and pressure fused to the top, rendering it firmly attached and highly sanitary. 1<sup>3</sup>/<sub>4</sub>" thick edge profile.

Base: Cut, formed and welded steel. 1.5" square steel tubing with 12 gauge structural members.

Made in the U.S.A.

**Installation**

None required

**Warranty**

10 year limited replacement warranty

**Maintenance**

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: When cleaning powder coated steel, Norix recommends the use of a cleaner made especially for stainless steel products.

## TESTING

**Performance Test Standards**

Tested to 1,000 lb static load

**Environmental Test Standards**

Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

## SPECIFICATIONS

**Model**

FO

**Weight**

48 lbs

**Dimensions**

Height 13.2"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

**Color**

Laminate Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve with black edge.

Base: Fossil, Moss

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Options**

Factory Ballasting (50 lbs)

\*Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

**Assembly**

None required

**Installation**

Required for ganging plates and ballast. Ballast weighting required to validate warranty. Recommend 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

**Warranty**

10 year limited replacement warranty.

**Fabrication & Material**

Top: Decorative high pressure laminate is bonded to a core of 45 lb density particle board with embedded T-nuts for securing top to base. Polyurethane edge is radiused for safety and pressure fused to the top, rendering it firmly attached and highly sanitary. 1<sup>3</sup>/<sub>4</sub>" thick edge profile.

Base: Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability. Molded-in steel threaded inserts for optional ganging side-to-side. Push in cap seals access port for sand or gravel ballast capability. Anti-ligature design with no internal openings. Made in the U.S.A.

**Maintenance**

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

**Performance Test Standards**

Tested to 1,000 lb static load

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials

## SPECIFICATIONS

**Model**

FO

**Weight**

32 lbs

**Dimensions**

Height 14.1"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

**Color**

Molded Top: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

Base: Maple, Teak, Walnut colored finish

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Assembly**

None required

**Fabrication & Material**

Top: One-piece, rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability.

Base: Glued mortise and tenon. 3" solid hardwood frame with tapered legs. Made in the U.S.A.

**Installation**

None required

**Warranty**

10 year limited replacement warranty

**Maintenance**

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Base: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

## TESTING

**Performance Test Standards**

Tested to 1,000 lb static load

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials

# Forté® Occasional Table - Molded Top with Steel Base

# NORIX®

## SPECIFICATIONS



### Model

FO

### Weight

29 lbs

### Dimensions

Height 13.5"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

### Color

Molded Top: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

Base: Metallic Silver

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Assembly

None required

### Fabrication & Material

Top: One-piece, rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability.

Base: Cut, formed and welded steel. 1.5" square steel tubing with 12 gauge structural members.

Made in the U.S.A.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Top: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcidex® or Oxivir Five 16®) per manufacturers' instructions.

Frame: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated steel.

## TESTING

### Performance Test Standards

Tested to 1,000 lb static load

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials

## SPECIFICATIONS

**Model**

FO

**Weight**

32.5 lbs

**Dimensions**

Height 14.6"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

**Color**

Molded Top: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

Base: Fossil, Moss

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Options**

Factory Ballasting (50 lbs)

\*Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

**Assembly**

None required

**Fabrication & Material**

One-piece, rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Anti-ligature design with no internal openings. Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

**Installation**

Required for ganging plates and ballast. Ballast weighting required to validate warranty. Recommend 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

**Warranty**

10 year limited replacement warranty

**Maintenance**

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

**Performance Test Standards**

Tested to 1,000 lb static load

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials