



Finishes

Stainless Steel.

Assembly

Shipped assembled.

**Intended for indoor use only*



Model	Weight		Width		Height		Depth	
	lbs	kg	in	cm	in	cm	in	cm
IGS-18-3	2.5	1.1	18"	45.7	3.1"	7.9	3"	7.6
IGS-24-3	3.7	1.7	24"	61				
IGS-36-3	5.2	2.4	36"	91.4				
IGS-42-3	5.9	2.7	42"	106.7				
IGS-48-3	6.9	3.1	48"	121.9				

Fabrication & Material

3⅛" (7.9 cm) dia. 11 gauge type 304 stainless steel flanges are heliarc welded to 1½" (3.8 cm) O.D. 18 gauge seamless tube. Suicide resistant 11 gauge closure plate is also heliarc welded to edge between tube and wall. Stainless steel #4 finish. Product designed with weep holes for liquid drainage that may build up within the grab bar. Product filled with water will be completely drained within 50 seconds.

Warranty

1 year limited replacement warranty.

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

Installation

Norix only recommends its products to be attached to solid concrete surfaces. For all other applications consult your professional installer for proper attachment. Installation hardware not supplied by Norix.

Performance Test Standards

- **18", 24", 36" and 42" Grab Bars:** Product tested to 250 lbs (113.4 kg) static load.
- **48" Grab Bar:** Product tested to 750 lbs (340.2 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.