

"L" Shaped Security Grab Bars



Finishes

Stainless Steel.

Options

- Right or left handed models.

Assembly

Shipped assembled.

**Intended for indoor use only*



Model	Weight		Dimensions		Height		Depth	
	lbs	kg	in	cm	in	cm	in	cm
IGS-1833-3	8	3.6	18" x 33"	45.7 x 83.8	3.1"	7.9	3"	7.6
IGS-3856-3	15	6.8	38" x 56"	96.5 x 142.2				

Fabrication & Material

3 1/8" (7.9 cm) dia. 11 gauge type 304 stainless steel flanges are heliarc welded to 1 1/2" (3.8 cm) O.D. 18 gauge seamless tube. Suicide resistant 11 gauge closure plate is also heliarc welded to edge between tube and wall. Stainless steel #4 finish. Product designed with weep gaps for liquid drainage.

Warranty

1 year limited replacement warranty.

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

Installation

Norix only recommends its products to be attached to solid concrete surfaces. For all other applications consult your professional installer for proper attachment. Installation hardware not supplied by Norix.

Performance Test Standards

- Product tested to 250 lbs (113.4 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. [UL.COM/GG](https://www.ul.com/gg).