SPECIFICATIONS



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Available in California TB133 compliant upholstery.

Upholstery

View our upholstery selections at www.norix. com/fabrics. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

| Model | Dimensions | | COM Yards | |
|-------------------------------|----------------|-------|-------------|------|
| LH-7 | Seat Height | 16.8" | Total Yards | 3.25 |
| Weight | Seat Width | 47" | Seat Yards | 2 |
| 149 lbs | Overall Height | 17.8" | Side Yards | 1.25 |
| | Depth | 24" | | |
| *Intended for indoor use only | Width | 54.3" | | |

Stinson



Fabrication & Material

The Harmony° Series is built around a robust fully welded steel frame for maximum durability. Plywood backers are wrapped in polyurethane foam and upholstered with a wide selection of fabrics while steel plates conceal staples and tamper resistant fasteners provide reinforced security. Polyurethane arm caps protect the vulnerable top and side edges while nylon feet protect floors. Made in the U.S.A.

Installation

None required

Warranty

5 year limited replacement warranty; lifetime structural warranty on internal steel frame. Refer to Norix[®] Terms and Conditions for details.

Maintenance

Easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

TESTING

Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. • Compliant with Healthier Hospitals guidelines

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

NORIX.COM