## Max-Master<sup>®</sup> Tables

## SPECIFICATIONS

DETAILS

Base: Metallic Silver, Black

Game Top with black edges.

for more accurate depiction of color.

Raven, Stainless Steel

Assembly

Color



Top: Kensington Maple, Asian Sun, Wild

Stainless Steel Tops: 304 stainless steel

Cherry, Montana Walnut with coordinating

edge. Titanium Evolve and Titanium Evolve

Seats: Canyon, Wild Berry, Meadow, Mojave,

Pine Cone, River Rock, Lagoon, Sea Spray,

\*Due to differences in monitors, printers and materials,

actual product colors may vary. Color chips are available

Secure base to top. Attach seats. Refer to

manufacturer's instructions for assembly.

#### Model/Weight

See Additional Dimensions on Page 2.

\*Intended for indoor use only

Dimensions Seat Height Height

19.8" 31.8"



#### **Fabrication & Material**

Legs: The curved, tubular steel that supports the top has a 10" radius bend to facilitate easy cleaning beneath the table. This curved piece is fully welded to a vertical steel tube that supports the seat. The top of the curved tubes and top of the seat tubes have fully welded  $6" \times 6" \times 1/4"$  thick steel mounting plates for installing top and seats. Bottom of seat tube has a fully welded mounting plate inset. For free standing applications, the inset is threaded to accommodate a tamper and skid-resistant, adjustable glide with a 1/2" diameter stem. For bolt-down application, the inset has a hole for the fully enclosed, tamper-resistant, bolt-down system. 3" diameter, 14 gauge steel tubing.

Standard Laminate Top: Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1/8" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" thick edge profile. Super Slammer Stone Seats: 13" diameter high-density, color-impregnated, compression-molded composite that is highly scratch and stain resistant. Four molded-in threaded inserts for superior metal-to-metal connection. Made in the U.S.A.

#### Installation

Fasten to the floor. No installation required on free standing models. Concealed concrete expansion anchors included with bolt-to-the-floor option.

### Warranty

10 year limited replacement warranty.

#### Maintenance

Laminate Tops: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green<sup>®</sup> or an equivalent cleaning product.

Legs and Stainless Steel Tops: When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

Legs: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of steel.

### **TESTING** -

#### **Performance Test Standards**

Product tested to 1.000 lb static load

#### **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG

• Complies with Healthier Hospitals guidelines

# **NORIX.COM**







## Max-Master® Table



## **Additonal Dimensions**

Models	<b>Top Dimensions</b>	Weight	<b>Foot Print Dimensions</b>	Height	
M44200	(42" Diameter)	183 lbs	(76" x 76")	Seat Height	19.8"
M65400	(54" Diameter)	270 lbs	(88" × 88")	Height	31.8"
M86000	(60" Diameter)	372 lbs	(94" × 94")		
M63072	(30" x 72")	280 lbs	(63" × 72")		
M83096	(30" × 96")	375 lbs	(63" x 72")		

#### Options

Glide Kit, Bolt-Down Kit

Seats: 12" diameter stainless steel #4 finish. Decreases seat height to 19.25", additionaly charge for upgrade

<u>Stainless Steel Quietcore Top</u>: Durable 18 gauge stainless steel top surface wrapped around sound deadening particle board core with embedded T-nuts. 1<sup>1</sup>/<sub>4</sub>" edge profile. (Available in the following sizes only - 42" round and 54" round).

<u>Rectangle Stainless Steel Top:</u> Stainless steel, 10 gauge, 304 stainless steel with a 1½" drop edge. Four stainless steel studs welded to the underside for attaching each leg. Changes height to 30.5" (Available in the following sizes only - 30"x72" and 30"x96").

ADA: ADA-compliant version with 30"x72", 30"x96", 42" round, 54" round and 60" round versions.

# NORIX.COM