

# Comfort Shield® Remedy Mattress

Black Max



Models	Weight		Dimensions		Height	
	lbs	kg	in	cm	in	cm
MRX6-2977	22	10	29" x 77"	73.7 x 195.6	6"	15.2
MRX6-3075	22	10	30" x 75"	76.2 x 190.5		
MRX6-3079	23	10.4	30" x 79"	76.2 x 200.7		
MRX6-3675	24	10.9	36" x 75"	91.4 x 190.5		
MRX6-3680	26	11.8	36" x 80"	91.4 x 203.2		
MRX6-3882	28.5	12.9	38" x 82"	96.5 x 208.3		

Note: Dimensional tolerances are +/- one inch.

## Finishes

See Design Guide for finish options.

## Options

Mattress is available with single or double integrated pillow.

## Assembly

Shipped assembled in poly bag.

\*Intended for indoor use only

## Fabrication & Material

### Sealed Seam Mattress

Comfortable polyurethane foam core is encased in a fortified ripstop, fire-retardant cover with radio frequency welded seams and reinforced stitching for enhanced hygiene, security and durability. Three-ply polyurethane coated cover is highly-puncture resistant and inhibits tearing if puncture does occur. Mattress is fluid, crack, peel, abrasion and bed bug resistant, anti-microbial and anti-fungal. Provides a virus barrier and is resistant to tearing and delaminating for greater infection control. Features a breathable vent that repels oil, water, blood, urine and other fluids. Made in the U.S.A.

## Warranty

5 year limited prorated warranty against seam failure and cover material cracking (Full warranty details available upon request).

## Maintenance

- Use hospital-grade cleaner or bleach/water solution on the entire mattress.
- Completely rinse with clean water (do not submerge).
- After cleaning, dry the mattress cover thoroughly. Do not place wet mattress onto a sleep surface; moisture may cause cover fabric damage (not covered by Limited Warranty).
- Contact Norix Customer Service for a mattress patch kit to address minor punctures and tears.

## Performance Test Standards

- Tested to ASTM F1566 Hexagonal Roller Mattress Durability Test
- Tested to ASTM D751 Hydrostatic Resistance Test for Coated Fabrics

## Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Flammability Test Standards

- 16 CFR Part 1633
- 16 CFR Part 1632
- California Technical Bulletin 129

