# Mix-Up<sup>™</sup> - Wedge



COM Yards

Total Yards

# **SPECIFICATIONS**



# Model MU960 Weight 16 lbs

\*Intended for indoor use only

**Dimensions** Width Depth Height

18.7″ 18.7″ 18″ 1.8



# DETAILS Base Color

#### Fossil, Raven, Moss

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

## Options

Upholstery upgradeable to TB133.

Factory Ballasting (15 lbs).

\*Ballastable up to 15 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

#### Upholstery

View our upholstery selections at <u>www.norix.</u> <u>com/fabrics</u>. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM. Upholstery flammability standard upgradable to TB133.

#### Assembly

None required

## Patents

Patents Pending

# **Fabrication & Material**

<u>Base:</u> Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning.

<u>Inside:</u> High-density flexible foam core designed to withstand high-traffic environments.

#### Installation

None required

#### Warranty

10 year limited replacement warranty

# Maintenance

Easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

# TESTING

## Performance Test Standards Product tested to 300 lbs static load Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

• Compliant with Healthier Hospitals guidelines

#### **Flammability Test Standards**

Compliant with the following flammability standards: State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

