

## SPECIFICATIONS



### Model

MU980

### Weight

57 lbs

### Dimensions

Diameter 36.6"  
Height 18"

### COM Yards

Total Yards 4.25

\*Intended for indoor use only



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Upholstery upgradeable to TB133.

Factory Ballasting (50 lbs).

\*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM. Upholstery flammability standard upgradeable to TB133.

### Assembly

None required

### Patents

Patents Pending

### Fabrication & Material

**Base:** Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning.

**Inside:** High-density flexible foam core designed to withstand high-traffic environments.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

## TESTING

### Performance Test Standards

Product tested to 500 lbs static load

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Flammability Test Standards

Compliant with the following flammability standards:

State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies