

Tank Box Property Storage

Standard



Fabrication & Material

Full height molded-in vertical ribs every 1¼". ½" x 7⁄8" (3.2 x 1.3 x 2.2 cm) top flange provides maximum strength and rigidity. Capable of nesting for stable stacking. Injection molded from structural polyethylene. 100% recyclable. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

Use

Only specially-designed, under-bunk Norix rails should be used in tandem with Tank Boxes. These rails are exclusive to Norix and are specifically made to be used with our boxes. An incorrect installation of rails and an erroneous rail/box fit may result when using custom-made rails or rails bought from other sources.

Performance Test Standards

- Minimum sustained static load of 3000 lbs (1,360.8 kg) for 4 hours.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items

Model PB200 (container)
PBL400 (lid)

Weight 9 lbs / 4.1 kg (container)
4 lbs / 1.8 kg (lid)

Dimensions (container)	in	cm
Width	22.9"	58.2
Depth	17.4"	44.2
Height	8.5"	21.6
Dimensions (lid)	in	cm
Width	23.1"	58.7
Depth	18"	45.7
Height	1.25"	3.2

Finishes

Raven

Options

- PBL400:** Optional lid with locating feature for stacking and hasp for locking.

Assembly

None required.

*Intended for indoor use only

