



Fabrication & Material

One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety, grooved sleep surface for fluid management. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation, contraband resistance and ligature resistant design. Contains a minimum of 45% recycled content. Made in the U.S.A.

Warranty

Lifetime warranty.

Maintenance

For routine and regular cleaning, Norix® recommends the use of Simple Green® or an equivalent cleaning product with a soft damp cloth. Prodigy® products are suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers’ instructions. Norix recommends inspecting fasteners after each use of the restraints, along with regular monthly inspections. Bolt-down fasteners should be tight with no gaps between the bottom of the bed and the floor. There should be no visible cracks in the caulk.

Installation

PRD100 - Proprietary ligature resistant floor anchoring system with concealed hardware (mechanism and all anchoring hardware included). Anchoring mechanism and hardware intended for concrete floors and/or walls. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring.
PRD100B - No installation necessary. Tamper-resistant non-removable steel encased floor glides are included and may be field installed.

Performance Test Standards

- **PRD100** - Tested to 1,500 lbs (680.4 kg) static load
- **PRD100B** - Tested to 1,500 lbs (680.4 kg) static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

Model PRD100 (Floor Mount)
PRD100B (Free-Standing)

Weight 130 lbs / 59 kg

Dimensions	in	cm
Overall Length	82"	208.3
Overall Width	38"	96.5
Height	18.5"	47
Bed Deck Length	80"	203.2
Bed Deck Width	36"	91.4

Note: Dimensional tolerances are +1% due to manufacturing process.

Mattress Size

36"x80" (91.4x203.2 cm)

Finishes

See Design Guide for finish options.

Options PRD100 (Floor Mount)

- Removable Restraint Ring Kit

*Ballasting and Post-production sealed bottom are not available on PRD100.

Options PRD100B (Free-Standing)

- Factory Ballasting of 100 lbs / 45.4 kg

*Factory Ballasting must be communicated at time of order, products are not field ballastable.

*Restraint Ring Kit, Bolt-down, Post-production Ballasting are not available on PRD100B. Bed type must be specified at time of order.

Patents

Patents Pending

*Intended for indoor use only

