

## SPECIFICATIONS



### Model

RA18

### Weight

51 lbs

\*Intended for indoor use only

### Dimensions

Seat Height 18.5"

Seat Width 21.8"

Overall Height 44"

Depth 45"

Width 27"



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

RA18-71: RockSmart 18" Heavier Weight

RA18-NR: RockSmart 18" No Runners

RA18-NR-71: RockSmart 18" No Runners

Heavier Weight

\*Ballasting is not available.

### Assembly

None required

### Installation

None required

### Patents

This product may be covered by US Patent 10,537,179 B2 and Patents Pending.

### Fabrication & Material

One-piece, rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Generous arc provides a relaxing and safe rocking action while securely affixed nylon runners protect floors. Rear bumper indicates the limits of safe rocking. Anti-ligature design with no internal openings. Made in the U.S.A.

### Warranty

10 year limited replacement warranty. The RockSmart® Rocker was designed to provide therapeutic rocking action. Nylon bumpers on the rear of the chair establish a stopping point to deter backward tipping. However, rocking aggressively may cause the chair to tip over. Do not stand on the RockSmart® chair.

### Maintenance

For routine and regular cleaning maintenance, Norix® recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

### Performance Test Standards:

- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items
- UL94 HB Test for Flammability of Plastic Materials
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture