

SPECIFICATIONS



Model

SD5836

Weight

9.5 lbs

*Intended for indoor use only

Dimensions

Door Width	35.5"
Hinge Width	1.5"
Overall Width	37"
Height	58"
Thickness	1.5"



DETAILS

Options

Left or Right hinge

*Must specify at time of order.

Colors

Choose from 8 designs



Riverstone



Autumn Waterfall



Tropical Beach



Golden Sunset



Spring Blossom



Cascading Waterfall



Pine



Teak

Fabrication & Material

SafeDoor from Norix Furniture provides a balance of safety and privacy in demanding environments. This unique door design hangs with magnetic nylon hinges that attach to metal door frames but collapse with just 20 pounds of force mitigating ligature risk. The high-quality vinyl material is RF welded over high-density polyurethane foam to withstand abuse. The hinge can withstand up to 500 lbs of pull force. SafeDoor is chemically resistant to bodily fluids and easy to clean. Made in the U.S.A.

Assembly

Shipped assembled in poly bag

Warranty

5 year limited prorated warranty against seam failure and cover material cracking. (Full warranty details available upon request.)

Maintenance

Use Simple Green® hospital-grade cleaner or bleach & water solution on the entire door. Completely rinse with clean water (do not submerge) & wipe with soft damp cloth. Do not use a brush as that may scuff the image.

Warning

Normal Neodymium magnets will lose their magnetic properties if heated above 175°F (80° C). The strong magnetic fields of neodymium magnets can damage items such as television, computer monitors, credit cards, bank cards, computers, diskettes and other data carriers, video tapes, mechanical watches, hearing aids, loud speakers and VCRs. Pace-makers may be damaged or switch to "Test Mode" in the presence of a strong magnetic force, if a pace-maker or other electrical body implant is in use, keep a minimum of 3 feet distance. Under no circumstances should you try to cut, saw or drill the Neodymium magnets.

TESTING

Material Test Standards

California Title 19, Sec. 12371 Small Scale test
NFPA 701-2015, Method 1

Flammability Test Standards

Compliant with the following flammability standards:

- ASTM E84
- State of California, Technical Bulletin No. 133, Flammability Test Procedure