

Terra Open Arm Sled Base Chair

NORIX

SPECIFICATIONS



Model

TA1	22"
TA2	30"

22" Seat

Open Arm	51.5 lbs
Half Arm	66.5 lbs
Full Arm	81.5 lbs

30" Seat

Open Arm	64.3 lbs
Half Arm	79.3 lbs
Full Arm	94.3 lbs

Dimensions

Seat Height	19"
Overall Height	34.8"
Overall Depth	26"
22" Overall Width	26.5"
30" Overall Width	34.5"

*Intended for indoor use only



DETAILS

Color

Frame: Metallic Silver, Black

Arm options: Wood (Walnut, Maple, & Teak) or Molded (Black)

Options

Available in California TB133 compliant upholstery. Bolt-down plate available.

Ballasting available:

25 lb plate for 22" Chair

35 lb plate for 30" Chair

*Ballasting must be communicated at time of order.

Assembly

No assembly required

Fabrication & Material

Frame: Welded steel frames

Cushions: Constructed of a 2.0 lb density seat foam wrapped in fabric with concealed staples.

Arm Caps: Hardwood (Maple, Teak, or Walnut color) or polyurethane in Raven

Arm Options: Open, Half Arm, & Full Arm panels are MDF, foam & fabric

Glides: Non-removable Nylon Glides

Installation

Required for bolt down

Warranty

10 year limited replacement

Maintenance

Frame: Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

Upholstery: Refer to upholstery manufacturer's cleaning instructions for specific fabric.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")