

# Terra

## Mixed Tandem Seating



Dimensions	in	cm
Seat Height	19.2"	48.8
Depth	26.2"	66.5

**Upholstery**

\*See pg. 2 for COM information.

\*View our upholstery selection on our website. Fabric Grades B - H and COM available.

### Finishes

See Design Guide for finish options.

### Options

- TB133 Upholstery Upgrade
  - Bolt-down Plate
  - Factory Ballasting with Steel Plates
- \*25 lb (11.3 kg) plate for 22" (55.9 cm) chair.  
 \*35 lb (15.9 kg) plate for 30" (76.2 cm) chair.  
 \*\*Ballasting must be communicated at time of order.

### Assembly

None required.

\*Intended for indoor use only

Model	Arm Style	Weight		Width		Height	
		lbs	kg	in	cm	in	cm
TC3 (22" left, 30" right, 2 Seat)	Open Arm	145	65.8	61"	154.9	34.8"	88.4
	Half Arm	177	80.3				
	Full Arm	209	94.8				
TC4 (30" left, 22" right, 2 Seat)	Open Arm	145	65.8	61"	154.9	34.8"	88.4
	Half Arm	177	80.3				
	Full Arm	209	94.8				

### Fabrication & Material

Terra mixed seating expands the offering of traditional tandem seating with configuration combinations of 22" (55.9 cm) and 30" (76.2 cm) seat sizes.

**Frame:** Welded steel arm frames

**Cushions:** Constructed of a 2.0 lb (0.9 kg) density seat foam wrapped in fabric with concealed staples.

**Arm Caps:** Hardwood (Maple, Teak, or Walnut color) or polyurethane in Raven

**Arm Options:** Open, Half Arm, & Full arm panels are MDF, foam & fabric

**Glides:** Non-removable Nylon Glides with secure hardware

### Warranty

10 year limited replacement.

### Maintenance

**Frame:** Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

**Upholstery:** Refer to upholstery manufacturer's cleaning instructions for specific fabric.

### Installation

Required for bolt-down.

### Performance Test Standards

- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 750 lb (340.2 kg) static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")(113.4 kg from 45.7 cm)

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.



### TC3 (22" left, 30" right)

Open Arm		
	yds	m <sup>3</sup>
<b>Total</b>	5.2	4.8
<b>Seat</b>	2	1.8
<b>Back</b>	3.2	2.9

Half Arm		
	yds	m <sup>3</sup>
<b>Total</b>	7.75	7.1
<b>Seat</b>	2	1.8
<b>Back</b>	3.2	2.9
<b>Arms</b>	2.55	2.3

Full Arm		
	yds	m <sup>3</sup>
<b>Total</b>	10.18	9.3
<b>Seat</b>	2	1.8
<b>Back</b>	3.2	2.9
<b>Arms</b>	4.98	4.6

### TC4 (30" left, 22" right)

Open Arm		
	yds	m <sup>3</sup>
<b>Total</b>	5.2	4.8
<b>Seat</b>	2	1.8
<b>Back</b>	3.2	2.9

Half Arm		
	yds	m <sup>3</sup>
<b>Total</b>	7.75	7.1
<b>Seat</b>	2	1.8
<b>Back</b>	3.2	2.9
<b>Arms</b>	2.55	2.3

Full Arm		
	yds	m <sup>3</sup>
<b>Total</b>	10.18	9.3
<b>Seat</b>	2	1.8
<b>Back</b>	3.2	2.9
<b>Arms</b>	4.98	4.6