

# Titan® Panel Base Bunk Bed

# NORIX®

## SPECIFICATIONS



### Model

TNT1151

### Weight

418 - 458 lbs

\*Intended for indoor use only

### Dimensions

Length 86"

Width 38.5"

Height 72"

### Recommended Mattress

36"x80"



## DETAILS

### Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Slate, Irish Moss, Dusk, Mink

\*Minimums apply

Laminate: Wild Cherry

Optional Laminate Colors: Kensington Maple, Rustic Slate, Pewter Brush

\*Minimums apply

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Steel Drawers Model TNT1052, Laminate Drawers Model TNT1252, Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Glide Kit, Bolt-down Kit, Bottom Closure Kit

### Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

### Fabrication & Material

Cut, formed, welded steel, powder coated steel.

Bed deck: 18 gauge

Body: 18 gauge

Gussets: 13 gauge

End frame legs: 16 gauge

End frame cross-members: 16 gauge

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).

Made in the U.S.A.

### Installation

None required for standard model

### Warranty

10 year limited replacement warranty

### Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Optional Decorative Laminate: Norix recommends the use of Simple Green® or an equivalent cleaning product.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

Tested to 800 lb static load