

# Titan® Bunkable Spring Deck Bed

# NORIX

## SPECIFICATIONS



### Model

TNT1311-0000

### Weight

92 lbs

\*Intended for indoor use only

### Dimensions

Length 85.8"

Width 38.5"

Height 37"

### Recommended Mattress

36"x80"



## DETAILS

### Color

Steel Color (Spring Deck): Matte Ebony

Steel Color (End Frames): Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Slate, Irish Moss, Dusk, Mink

\*Minimums apply

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Bolt-down Kit, Bunk Lock Clamps, Glide kit

### Assembly

Attach wedge lock brackets to end frames with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Secure spring deck bolts to wedge lock slots. Optional accessories attach to bed (with hardware supplied through purchase of accessories).

### Fabrication & Material

Cut, formed, welded steel, powder coated steel.

Bed deck: 2" x 1/5" x 5/32" rail angle steel, sinuous 9 gauge wire connected by 13 gauge links with 12 gauge 16 turn helical springs.

End frame legs: 16 gauge

End frame cross-members: 16 gauge

End Caps: Injection molded high-impact plastic

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).

Made in the U.S.A.

### Installation

None required for standard model

### Warranty

10 year limited replacement warranty

### Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Optional Decorative Laminate: Norix recommends the use of Simple Green® or an equivalent cleaning product.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

Tested to 800 lb static load