



Fabrication & Material

Cut, formed, welded steel, powder coated steel
Bed deck: 12 gauge
End frame legs: 16 gauge
End frame cross-members: 16 gauge
Connector Brackets: 3/8" (1 cm) thick
End Caps: Injection molded high-impact plastic
Optional Headboard: 45 lb (20.4 kg) density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).
Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.
Optional Decorative Laminate: Norix recommends the use of Simple Green[®] or an equivalent cleaning product.
Norix recommends inspecting fasteners after each use of the restraints, along with regular monthly inspections. Bolt-down fasteners should be tight with no play between the bolt-down bracket and the floor.

Performance Test Standards

- Tested to 1,000 lbs (453.6 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Model	TNT1611-0003
Weight	124 lbs / 56.2 kg

Dimensions	in	cm
Length	81.2"	206.2
Width	38.5"	97.8
Height	37.1"	94.2

Mattress Size
36"x75" (91.4x109.5 cm)

Finishes
See Design Guide for finish options.

- Options
- Headboard & Footboard
 - Ladder
 - Safety Rail
 - Bunk Lock Clamps
 - Glide Kit
 - Bolt-down Kit

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

*Intended for indoor use only

