# Titan<sup>®</sup> Bunkable Frame Style Bed - Steel Deck



# **SPECIFICATIONS**



#### Model

TNT1611-0004

### Weight

188 lbs

\*Intended for indoor use only

#### **Dimensions**

 Length
 86.5"

 Width
 56.5"

 Height
 37"

# **Recommended Mattress**

54"x80"





# **DETAILS**

#### **Finishes**

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### **Options**

Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Bolt-down Kit, Bunk Lock Clamps, Glide kit

## **Assembly**

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

#### **Fabrication & Material**

Cut, formed, welded steel, powder coated steel

<u>Bed deck:</u> 12 gauge <u>End frame legs:</u> 16 gauge

End frame cross-members: 16 gauge

Connector Brackets: 3/8" thick

End Caps: Injection molded high-impact plastic

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).

Made in the U.S.A.

#### Installation

None required for standard model

#### Warranty

10 year limited replacement warranty

## Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Optional Decorative Laminate: Norix recommends the use of Simple Green\* or an equivalent cleaning product.

## **TESTING**

# **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

# **Performance Test Standards**

Tested to 1,000 lb static load