

SPECIFICATIONS

**Model**

TNT1750-0000

Weight

167-227 lbs

*Intended for indoor use only

Dimensions

Length 86.2"

Width 38.5"

Height 72"

Recommended Mattress

36"x80"



DETAILS

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

*Minimums apply

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Glide Kit

Assembly

Attach end frames to bed deck with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Optional accessories attach to bed (with hardware supplied through purchase of accessories). Attach fulllength Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

Fabrication & Material

Cut, formed, welded steel, powder coated steel.

Bed deck: 12 gaugeEnd frame legs: 16 gaugeEnd frame cross members: 16 gaugeDesk Top/Fascia: High-pressure laminate over 3/4" 7-ply plywood substrate with 3mm PVC edge band.Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).

Made in the U.S.A.

Installation

None required for standard model

Warranty

10 year limited replacement warranty

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Optional Decorative Laminate: Norix recommends the use of Simple Green® or an equivalent cleaning product.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

Tested to 1,000 lb static load