

SPECIFICATIONS

**Model**

TNT1850-0003

Weight

118 - 126 lbs

*Intended for indoor use only

Dimensions

Length 80.6"

Width 37.5"

Height 72"

Recommended Mattress

36"x75"



DETAILS

ColorSteel Color (Spring Deck): Matte EbonySteel Color (End Frames): Khaki, EbonyOptional Steel Colors (End Frames Only):

Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

*Minimums apply

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Glide Kit

Assembly

Attach wedge lock brackets to end frames with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Secure spring deck bolts to wedge lock slots. Attach fascia/safety rail and headboard to end frames with furnished fasteners. Attach full-length Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

Fabrication & Material

Cut, formed, welded steel, powder coated steel

Bed deck: 2" x 1.5" x 5/32" rail angle steel, sinuous 9 gauge wire connected by 13 gauge links with 12 gauge 16 turn helical springs. 8 gauge spring deck connector brackets.End frame legs: 16 gaugeEnd frame cross members: 16 gaugeDesk Top/Fascia: High-pressure laminate over 3/4" 7-ply plywood substrate with 3mm PVC edge bandOptional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge (Wild Cherry Standard).

Made in the U.S.A.

Installation

None required for standard model

Warranty

10 year limited replacement warranty

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

Optional Decorative Laminate: Norix recommends the use of Simple Green® or an equivalent cleaning product.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

- Tested to 800 lb static load