## Titan<sup>®</sup> Loft Bed - Spring Deck

## SPECIFICATIONS



Model

TNT1850 **Weight** 126 - 186 lbs

\*Intended for indoor use only

# NORX

Dimensions Length 85.6" Width 38.5" Height 72" Recommended Mattress 36"x80"



## DETAILS

#### Color

<u>Steel Color (Spring Deck)</u>: Matte Ebony <u>Steel Color (End Frames)</u>: Khaki, Ebony <u>Optional Steel Colors (End Frames Only)</u>: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

\*Minimums apply

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

#### Options

Headboard & footboard (Wild Cherry Standard), Ladder, Safety rail, Glide Kit

#### Assembly

Attach wedge lock brackets to end frames with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Secure spring deck bolts to wedge lock slots. Attach fascia/safety rail and headboard to end frames with furnished fasteners. Attach full-length Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

### **TESTING**

#### Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

• Compliant with Healthier Hospitals guidelines

## Performance Test Standards

Tested to 800 lb static load

#### Fabrication & Material

Cut, formed, welded steel, powder coated steel.

<u>Bed deck:</u> 2" x 1.5" x <sup>5</sup>/<sub>32</sub>" rail angle steel, sinuous 9 gauge wire connected by 13 gauge links with 12 gauge 16 turn helical springs. 8 gauge spring deck connector brackets. <u>End frame legs:</u> 16 gauge

End frame cross members: 16 gauge

<u>Desk Top/Fascia</u>: High-pressure laminate over <sup>3</sup>/<sub>4</sub>" 7-ply plywood substrate with 3mm PVC edge band.

Optional Headboard: 45 lb density M3 grade particle board with durable highpressure laminate surface and 2mm PVC edge (Wild Cherry Standard).

Made in the U.S.A.

#### Installation

None required for standard model

#### Warranty

10 year limited replacement warranty

#### Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.

<u>Optional Decorative Laminate:</u> Norix recommends the use of Simple Green<sup>®</sup> or an equivalent cleaning product.

# NORIX.COM