NORIX

SPECIFICATIONS



Model
VA600
Weight 30 lbs
*Intended for indoor use only

Dimensions	
Seat Height	18.2"
Seat Width	19"
Overall Height	33"
Overall Depth	26.6"
Width	24"
Arm Height	25.7"

COM Ya	rds
--------	-----

Total Yards









1

DETAILS

Calar

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Optional upholstered plywood shell comes factory installed and can be easily removed for cleaning or replacement. Cushioned comfort provided by polyurethane foam on back and seat. Upholstered flammability standard upgradeable to TB133.

Bolt-Down Kit, Factory Ballasting (50 lbs). *Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Fabrication & Material

One-piece rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Anti-ligature design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty

Stinson

10 year limited replacement warranty

Maintenance

<u>Seats:</u> For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Optional Upholstery: Refer to Upholstery Manufacturers' cleaning instructions.

TESTING

Performance Test Standards

- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")
- Tested to 750 lb. static load

Environmental Test Standards

- •GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards

Compliant with the following flammability standards: Upholstered Chair:

• State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

Non-Upholstered Chair:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items