Vesta Lounge Arm Chair

SPECIFICATIONS



TruColor

USA

PRODUCT



Canyon, Wild Berry, Meadow, Mojave, Pine

*Due to differences in monitors, printers and materials,

actual product colors may vary. Color chips are available

Optional upholstered plywood shell comes

factory installed and can be easily removed

comfort provided by polyurethane foam on

for cleaning or replacement. Cushioned

back and seat. Upholstered flammability

standard upgradeable to TB133.

Cone, River Rock, Lagoon, Graphite, Sea

for more accurate depiction of color.

Model	Dimensions		COM Yards	
VA620	Seat Height	18.2"	Total Yards	1.15
Weight	Seat Width	21"		
34 lbs	Overall Height	33"		
	Overall Depth	31.3"		
*Intended for indoor use only	Width	27"		
	Arm Height	25.6"		

Stinson SEE / SAMPLE / SPEC

Fabrication & Material

One-piece rotationally-molded polyethylene with lightly textured maintenancefree surface which allows for easy cleaning. Anti-ligature design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor[™] polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty

10 year limited replacement warranty

Maintenance

<u>Seats:</u> For routine and regular cleaning maintenance, Norix recommends the use of Simple Green[®] or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex[®], Wexcide[®] or Oxivir Five 16[®]) per manufacturers' instructions. <u>Optional Upholstery:</u> Refer to Upholstery Manufacturer's cleaning instructions.

Bolt-Down Kit, Factory Ballasting (50 lbs).

DETAILS

Color

Spray

Options

*Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at <u>www.norix.</u> <u>com/fabrics</u>. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

TESTING

Performance Test Standards

• Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

• Tested to 1,000 lb static load

Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7

• Compliant with Healthier Hospitals guidelines

Flammability Test Standards

Compliant with the following flammability standards: <u>Upholstered Chair</u>:

• State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

Non-Upholstered Chair:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

NORIX.COM

One Innovation Drive, West Chicago, IL 60185 | Phone: 630-231-1331 | Toll Free: 800-234-4900 | Email: furniture@norix.com Specifications subject to change without notice. | @2021 Norix Group, Inc. | All Rights Reserved. | Printed in U.S.A. 5/21