## **SPECIFICATIONS**



TruColo

COLOF

USA

Model	Dimensions		COM Yards	
VA630	Seat Height	18.2"	Total Yards	1.15
Weight	Seat Width	27"		
30 lbs	Overall Height	33"		
	Overall Depth	31.3"		
*Intended for indoor use only	Width	27"		

### DETAILS

#### Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

#### Options

Optional upholstered plywood shell comes factory installed and can be easily removed for cleaning or replacement. Cushioned comfort provided by polyurethane foam on back and seat. Upholstered flammability standard upgradeable to TB133. Bolt-Down Kit, Ballastable on site or at factory.

#### Upholstery

View our upholstery selections at www.norix. com/fabrics. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

#### Assembly

None required

## **Fabrication & Material**

Stinson

One-piece, rotationally-molded polyethylene with lightly textured maintenancefree surface which allows for easy cleaning. Anti-ligature design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with a threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution, and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

#### Warrantv

10 year limited replacement warranty

#### Maintenance

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green<sup>®</sup> or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox<sup>°</sup> Clean-Up<sup>°</sup> Cleaner + Bleach or an equivalent cleaning solution.

Optional Upholstery: Refer to Upholstery Manufacturer's cleaning instructions.

### TESTING

#### **Performance Test Standards**

• Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

## • Tested to 1,000 lb static load

#### **Environmental Test Standards**

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/ GG. Plastic is Recyclable #7

• Compliant with Healthier Hospitals guidelines

#### **Flammability Test Standards**

Compliant with the following flammability standards:

- Upholstered Chair: State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Non-Upholstered Chair: State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

# NORIX.COM

One Innovation Drive, West Chicago, IL 60185 | Phone: 630-231-1331 | Toll Free: 800-234-4900 | Email: furniture@norix.com Specifications subject to change without notice. | @2021 Norix Group, Inc. | All Rights Reserved. | Printed in U.S.A. 3/21