Vesta Lounge Armless Chair



SPECIFICATIONS



Model	Dimensions		COM Yards	
VA630	Seat Height	18.2"	Total Yards	1.15
Weight	Seat Width	27"		
30 lbs	Overall Height	33"		
	Overall Depth	31.3"		
*Intended for indoor use only	Width	27"		









DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Optional upholstered plywood shell comes factory installed and can be easily removed for cleaning or replacement. Cushioned comfort provided by polyurethane foam on back and seat. Upholstered flammability standard upgradeable to TB133.

Bolt-Down Kit, Factory Ballasting (50 lbs). *Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Fabrication & Material

One-piece, rotationally-molded polyethylene with lightly textured maintenance-free surface which allows for easy cleaning. Anti-ligature design with no internal openings. Tamper-resistant steel-encased nylon glides for floor protection. Molded-in access port with a threaded screw cap for ballast weighting capability. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution, and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warrantv

10 year limited replacement warranty

Maintenance

<u>Seats:</u> For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Optional Upholstery: Refer to Upholstery Manufacturer's cleaning instructions.

TESTING -

Performance Test Standards

- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")
- Tested to 1,000 lb static load

Environmental Test Standards

- •GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards

Compliant with the following flammability standards: Upholstered Chair:

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies Non-Upholstered Chair:
- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- for low chemical emissions to UL 2818. UL.COM/ State of California, Technical Bulletin No. 117, Flammability Test Procedure for GG. Plastic is Recyclable #7 Seating Furniture for Use in Public Occupancies
 - UL1056 Fire Test of Upholstered Furniture
 - $\bullet \, \mathsf{ASTM} \,\, \mathsf{E1537} \, \mathsf{Test} \,\, \mathsf{Method} \, \mathsf{for} \, \mathsf{Fire} \, \mathsf{Testing} \, \mathsf{of} \, \mathsf{Real} \, \mathsf{Scale} \, \mathsf{Upholstered} \, \mathsf{Furniture} \, \mathsf{Items} \, \mathsf{Items}$