

## SPECIFICATIONS

**Model**

FC630/FC670

**Weight**

40.5 lbs

\*Intended for indoor use only

**Dimensions**

Seat Height 17"

Seat Width 27"

Overall Height 31.6"

Depth 30.9"

Width 27"

**COM Yards**

Total Yards 1.15

Stinson  
SEE / SAMPLE / SPEC

## DETAILS

**Finishes**

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Options**

Optional upholstered plywood shell comes factory installed and can be easily removed for cleaning or replacement. Cushioned comfort provided by polyurethane foam on back and seat. Upholstered flammability standard upgradeable to TB133.

Ganging Kit, Bolt-Down Kit

**Upholstery**

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

**Patents**

Patents Pending

**Fabrication & Material**

**Seat:** One-piece rotationally-molded polyethylene with lightly textured maintenance free surface allows for easy cleaning. High-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

**Base:** Cut, formed and welded steel. Molded-in steel threaded inserts for optional ganging side-to-side. 1.5" square steel tubing with 12 gauge structural members. Made in the U.S.A.

**Assembly**

None required

**Installation**

Required for ganging plates

**Warranty**

10 year limited replacement warranty

**Maintenance**

**Seats:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

**Base:** When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

**Optional Upholstery:** Refer to Upholstery Manufacturer's cleaning instructions.

## TESTING

**Performance Test Standards**

- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Compliant with the following flammability standards:

- **Upholstered Chair:** State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- **Non-Upholstered Chair:** State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)