

Titan®

Lift Deck Bed



Fabrication & Material

Cut, formed, welded steel, powder coated steel.
Bed deck: 12 gauge
Body: 18 gauge
Bottom: 18 gauge
End frame legs: 16 gauge
End frame cross-members: 16 gauge
End Caps: Injection molded high-impact plastic

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder coated steel.
Norix recommends inspecting fasteners after each use of the restraints, along with regular monthly inspections. Bolt-down fasteners should be tight with no play between the bolt-down bracket and the floor.

Performance Test Standards

- Tested to 800 lbs (362.9 kg) static load.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Model	TNT1616
Weight	253 lbs / 114.8 kg

Dimensions	in	cm
Length	86"	218.4
Width	38.5"	97.8
Height	37"	94

Mattress Size
36"x80" (91.4x203.2 cm)

Finishes
See Design Guide for finish options.

Assembly
Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame).

**Intended for indoor use only*

