

## SPECIFICATIONS



### Model

ATN620

### Weight

Desk without top 45 lbs

Desk with top 65 lbs

### Dimensions

Width 35.5"

Depth 23.7"

Height without top 23.8"

Height with top 24.8"

Note: Dimensional tolerances are +1% due to manufacturing process.

\*Intended for indoor use only



## DETAILS

### Color

Base: Pine Cone, River Rock, Lagoon, Graphite

Optional Laminate Top: Kensington Maple, Asian Sun, Wild Cherry, and Montana Walnut with a color coordinated molded edge.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

ATN620: Without Laminate

ATN621: Without Laminate and without Bottom Cores

ATN625: With Laminate

### Assembly

None required

### Patents

This product may be covered by US Patent No. US 8,007,059 B2.

### Fabrication & Material

Base: Slightly textured, maintenance-free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Anti-ligature design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption.

Optional Laminate Top: 45 lb density M3 grade particle board with embedded T-nuts for mechanically attaching top to base with a secure steel-to-steel connection.

Decorative high-pressure laminate sealed with a specially formulated, highly durable molded edge. Edge is radiused for safety and pressure fused to the top, making it highly sanitary. Made in the U.S.A.

### Installation

Anchors required for permanently attaching to solid wall. Anchors not supplied by Norix. Groove along mounting surface for caulk application (caulk not supplied by Norix).

### Warranty

10 year limited replacement warranty. Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F with a relative humidity of 35%.

### Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

### Performance Test Standards

Product tested to 1,000 static load

### Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture