

SPECIFICATIONS



Model

ATN700

Weight

Standard 63 lbs

Deluxe 76 lbs

Note: Dimensional tolerances are +1% due to manufacturing process.

Dimensions

Width 30"

Depth 18"

Height without top 42"

Height with top 42.8"

Total Volume 7 cu. ft.

Cubby Volume 2.4 cu. ft.

*Intended for indoor use



DETAILS

Color

Base: Pine Cone, River Rock, Lagoon, Graphite

Optional Laminate Top: Kensington Maple, Asian Sun, Wild Cherry, and Montana Walnut with a color coordinated molded edge.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

ATN700: Open Chest without Laminate

ATN750: Deluxe Open Chest with Laminate

Assembly

None required

Patents

This product may be covered by US Patent No. US 8,007,059 B2.

Fabrication & Material

Base: Slightly textured, maintenance-free surface allows for easy cleaning. Rotationally molded, specially formulated, anti-ligature, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Anti-ligature design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption.

Optional Laminate Top: 45 lb density M3 grade particle board with embedded T-nuts for mechanically attaching top to base with a secure steel-to-steel connection. Decorative high-pressure laminate sealed with a specially formulated, highly durable molded edge. Edge is radiused for safety and pressure fused to the top, making it highly sanitary. Made in the U.S.A.

Installation

Anchors required for permanently attaching to floor. Anchors not supplied by Norix. Groove along mounting surface for caulk application (caulk not supplied by Norix).

Warranty

10 year limited replacement warranty. Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda products shipped via ocean container maintain a temperature of 70-75°F with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda products are bleach cleanable and suitable for use with hospital-grade disinfectants (such as Clorox® Clean-Up Cleaner + Bleach, Virex® or Wexcide®).

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture