# **SPECIFICATIONS**



 22" TC1/TE1

 30" TC2/TE2

 **Dimensions** 

 Seat Height
 19"

 Overall Height
 34.8"

 Overall Depth
 26"

 22" 2 Seat Width
 50.5"

 30" 2 Seat Width
 66.5"

 22" 3 Seat Width
 74.5"

 30" 3 Seat Width
 98.5"

Model

Weight	22" 2 Seat	22" 3 Seat
Open Arm	93 lbs	154.5 lbs
Half Arm	115.5 lbs	184.5 lbs
Full Arm	138 lbs	214.5 lbs
	30″ 2 Seat	30″ 3 Seat
Open Arm	118.6 lbs	192.9 lbs
Half Arm	141.1 lbs	222.9 lbs
Full Arm	163.6 lbs	252.9 lbs

\*Intended for indoor use only

#### See page 2 for COM information.



## DETAILS

#### Color

<u>Frame:</u> Metallic Silver, Black <u>Arm options:</u> Wood (Walnut, Maple, & Teak) or Molded (Black)

#### Options

Available in California TB133 compliant upholstery. Bolt-down plate. <u>Ballasting available:</u> 25 lb plate for 22" Chair 35 lb plate for 30" Chair \*Ballasting must be communicated at time of order.

#### Assembly

No assembly required

### **Fabrication & Material**

Frame: Welded steel arm frames

<u>Cushions:</u> Constructed of a 2.0 lb density seat foam wrapped in fabric with concealed staples.

<u>Arm Caps:</u> Hardwood (Maple, Teak, or Walnut color) or polyurethane in Raven <u>Arm Options:</u> Open, Half Arm, & Full arm panels are MDF, foam & fabric <u>Glides:</u> Non-removable Nylon Glides with secure hardware

#### Installation

Required for bolt-down

#### Warranty

10 year limited replacement

#### Maintenance

<u>Frame:</u> Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

<u>Upholstery:</u> Refer to upholstery manufacturer's cleaning instructions for specific fabric.

# TESTING

## Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

• Compliant with Healthier Hospitals guidelines

#### **Performance Test Standards**

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

# NORIX.COM



# COM YARDS -

TC1 - 22" Open	Arm Chair	TC1 - 22" Half Arm Chair		TC1 - 22" Full A	TC1 - 22" Full Arm Chair	
Total Yards	4.6	Total Yards	7.15	Total Yards	9.58	
Seat Yards	2	Seat Yards	2	Seat Yards	2	
Back Yards	2.6	Back Yards	2.6	Back Yards	2.6	
		Arm Yards	2.55	Arm Yards	4.98	
TE1 - 22" Open Arm Chair		TE1 - 22" Half Arm Chair		TE1 - 22" Full Arm Chair		
Total Yards	6.9	Total Yards	10.3	Total Yards	13.54	
Seat Yards	3	Seat Yards	3	Seat Yards	3	
Back Yards	3.9	Back Yards	3.9	Back Yards	3.9	
		Arm Yards	3.4	Arm Yards	6.64	
TC2 - 22" Open Arm Chair		TC2 - 22" Half Arm Chair		TC2 - 22" Full Arm Chair		
Total Yards	5.6	Total Yards	9	Total Yards	10.58	
Seat Yards	2	Seat Yards	2	Seat Yards	2	
Back Yards	3.6	Back Yards	3.6	Back Yards	3.6	
		Arm Yards	3.4	Arm Yards	4.98	
TE2 - 22" Open Arm Chair		TE2 - 22" Half Arm Chair		TE2 - 22" Full Arm Chair		
Total Yards	8.4	Total Yards	11.8	Total Yards	15.04	
Seat Yards	3	Seat Yards	3	Seat Yards	3	
Back Yards	5.4	Back Yards	5.4	Back Yards	5.4	
	5.4	DACK TATUS	5.4	Dack laius	0.4	



NORIX