

Terra

2 & 3 Seat Tandem Sled Base Chair



Dimensions	in	cm
Seat Height	19"	48.3
Depth	26"	66
Upholstery		
*See pg. 2 for COM information.		

*View our upholstery selection on our website.
Fabric Grades B - H and COM available.

Finishes

See Design Guide for finish options.

Options

- TB133 Upholstery Upgrade
- Bolt-down Plate
- Factory Ballasting with Steel Plates

*25 lb (11.3 kg) plate for 22" (55.9 cm) chair.
*35 lb (15.9 kg) plate for 30" (76.2 cm) chair.
**Ballasting must be communicated at time of order.

Assembly

None required.

*Intended for indoor use only

Model	Arm Style	Weight		Width		Height			
		lbs	kg	in	cm	in	cm		
TC1 <i>(22", 2 Seat)</i>	Open Arm	93	42.2	50.5"	128.3	34.8"	88.4		
	Half Arm	115.5	52.4						
	Full Arm	138	62.6						
TC2 <i>(30", 2 Seat)</i>	Open Arn	118.6	53.8	66.5"	168.9				
	Half Arm	141.1	64						
	Full Arm	163.6	74.2						
TE1 <i>(22", 3 Seat)</i>	Open Arm	154.5	70.1	74.5"	189.2				
	Half Arm	184.5	83.7						
	Full Arm	214.5	97.3						
TE2 <i>(30", 3 Seat)</i>	Open Arn	192.9	87.5	98.5"	250.2				
	Half Arm	222.9	101.1						
	Full Arm	252.9	114.7						

Fabrication & Material

Frame: Welded steel arm frames

Cushions: Constructed of a 2.0 lb (0.9 kg) density seat foam wrapped in fabric with concealed staples.

Arm Caps: Hardwood (Maple, Teak, or Walnut color) or polyurethane in Raven

Arm Options: Open, Half Arm, & Full arm panels are MDF, foam & fabric

Glides: Non-removable Nylon Glides with secure hardware

Warranty

10 year limited replacement.

Maintenance

Frame: Norix recommends the use of soap and water or cleaner made for stainless steel for both regular and deep cleaning.

Upholstery: Refer to upholstery manufacturer's cleaning instructions for specific fabric.

Installation

Required for bolt-down.

Performance Test Standards

- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 750 lb (340.2 kg) static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")(113.4 kg from 45.7 cm)

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.



Terra

2 & 3 Seat Tandem Sled Base Chair



TC1 (22", 2 Seat)			TC2 (30", 2 Seat)			TE1 (22", 3 Seat)			TE2 (30", 3 Seat)		
Open Arm			Open Arm			Open Arm			Open Arm		
	yds	m ³		yds	m ³		yds	m ³		yds	m ³
Total	4.6	4.2	Total	5.6	5.1	Total	6.9	6.3	Total	8.4	7.7
Seat	2	1.8	Seat	2	1.8	Seat	3	2.7	Seat	3	2.7
Back	2.6	2.4	Back	3.6	3.3	Back	3.9	3.6	Back	5.4	4.9
Half Arm			Half Arm			Half Arm			Half Arm		
	yds	m ³		yds	m ³		yds	m ³		yds	m ³
Total	7.15	6.5	Total	9	8.2	Total	10.3	9.4	Total	11.8	10.8
Seat	2	1.8	Seat	2	1.8	Seat	3	2.7	Seat	3	2.7
Back	2.6	2.4	Back	3.6	3.3	Back	3.9	3.6	Back	5.4	4.9
Arms	2.55	2.3	Arms	3.4	3.1	Arms	3.4	3.1	Arms	3.4	3.1
Full Arm			Full Arm			Full Arm			Full Arm		
	yds	m ³		yds	m ³		yds	m ³		yds	m ³
Total	9.58	8.8	Total	10.58	9.7	Total	13.54	12.5	Total	15.04	13.8
Seat	2	1.8	Seat	2	1.8	Seat	3	2.7	Seat	3	2.7
Back	2.6	2.4	Back	3.6	3.3	Back	3.9	3.6	Back	5.4	4.9
Arms	4.98	4.6	Arms	4.98	4.6	Arms	6.64	6.1	Arms	6.64	6.1