

## SPECIFICATIONS

**Model**

WC10

**Weight**

42 lbs

\*Intended for indoor use only

**Dimensions**

Seat Height 18.5"

Seat Width 22"

Overall Height 31.4"

Depth 18.7"

Width 22"

Arm Height 25.4"

**COM Yards**

Total Yards 2.4

Seat Yards 1

Back Yards 1.4

Stinson  
SEE / SAMPLE / SPEC

## DETAILS

**Color**

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Options**

Ganging kit, Bolt-down kit, Ballast: Dry pea gravel 50 lbs recommended, 70 lbs maximum.

Replacement cushions are available and easily installed in the field. Seat and backs are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

**Upholstery**

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

**Assembly**

None required

**Installation**

Required for ganging plates and ballast. Recommended 50 lbs of I ballast. Ballast not supplied by Norix.

**Fabrication & Material**

**Frame:** One-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading) is chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Molded-in access port with threaded screw cap for ballast weighting capability. Non-removable steel encased nylon glides for floor protection.

**Back:** 5" polyurethane foam is fully upholstered and stapled to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection.

**Seat:** Upholstered 4" polyurethane foam with a 6" bullnose glued to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection. The seat features both a side and back clean-out for easy cleaning. Made in the U.S.A.

**Warranty**

10 year limited replacement warranty

**Maintenance**

**Frame:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

**Upholstery:** Refer to Upholstery Manufacturer's cleaning instructions.

## TESTING

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Optional upgrade for compliance with the following standards:

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

**Performance Test Standards**

- Tested to 750 lb static load
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012