

Kube Right Arm Chair



SPECIFICATIONS



Model

KE12R

Weight

24 lbs

Dimensions

| | |
|-------------|-----|
| Height | 29" |
| Arm Height | 21" |
| Seat Height | 16" |
| Depth | 28" |
| Width | 28" |

COM Yards

Total Yards 2.75



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Bolt-Down, Ganging Kit,

Upholstery upgradeable to TB133.

Factory Ballasting (50 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade B,

Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, Grade I, Grade J, Grade K, Grade L, and COM. Upholstery flammability standard upgradeable to TB133.

Assembly

None required

Patents

Patents Pending

Fabrication & Material

Base: Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning.

Cushion: 2" thick open cell foam adhered to EPP high density flexible foam is attached at 6 locations to base with tamper-resistant SST hardware for outdoor use.

Installation

None required

Warranty

5 year limited replacement warranty

Maintenance

Base: Easily cleaned with a damp cloth and a mild soap solution.

Seat: Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

TESTING

Performance Test Standards

Product tested to 1,000 lbs static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items