

SPECIFICATIONS



Model

KE50

Weight

17 lbs

Dimensions

Height 12.1"

Depth 28"

Width 28"



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Bolt-Down, Ganging Kit,
Factory Ballasting (50 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required

Patents

Patents Pending

Fabrication & Material

Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning.

Installation

None required

Warranty

5 year limited replacement warranty

Maintenance

Easily cleaned with a damp cloth and a mild soap solution.

TESTING

Performance Test Standards

Product tested to 1,000 lbs static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items