

## SPECIFICATIONS



### Model

KE11

### Weight

23 lbs

### Dimensions

Seat Height	16"
Seat Depth	20"
Overall Height	29"
Depth	28"
Width	28"

### COM Yards

Total Yards 2.75



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Bolt-Down, Ganging Kit,  
Factory Ballasting (50 lbs).

\*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade C, Grade F, Grade G, Grade H, Grade I, Grade J, Grade K, Grade L, and COM.

### Assembly

None required

### Patents

Patents Pending

### Fabrication & Material

**Base:** Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Adjustable removable glides to stabilize for un-even surfaces.

**Cushion:** 2" thick open cell foam adhered to EPP high density flexible foam is attached to base with heavy duty velcro.

### Installation

None required

### Warranty

5 year limited replacement warranty

### Maintenance

**Base:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

**Seat:** Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

## TESTING

### Performance Test Standards

Product tested to 500 lbs static load

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.