

SPECIFICATIONS



Model

KE13

Weight

25.5 lbs

Dimensions

Height	29"
Seat Height	16"
Seat Depth	20"
Depth	28"
Width	28"

COM Yards

Total Yards 2.5



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.chips are available for more accurate depiction of color.

Options

Bolt-Down, Ganging Kit,
Factory Ballasting (50 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade C, Grade F, Grade G, Grade H, Grade I, Grade J, Grade K, Grade L, and COM.

Assembly

None required

Patents

Patents Pending

Fabrication & Material

Base: Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Adjustable removable glides to stabilize for un-even surfaces.

Cushion: 2" thick open cell foam adhered to EPP high density flexible foam is attached to base with heavy duty velcro.

Installation

None required

Warranty

5 year limited replacement warranty

Maintenance

Base: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

Seat: Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

TESTING

Performance Test Standards

Product tested to 500 lbs static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.