

SPECIFICATIONS



Model

KE50

Weight

17 lbs

Dimensions

Height 12.1"

Depth 28"

Width 28"



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Bolt-Down, Ganging Kit,
Factory Ballasting (50 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Assembly

None required

Patents

Patents Pending

Fabrication & Material

Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning. Adjustable removable glides to stabilize for un-even surfaces.

Installation

None required

Warranty

5 year limited replacement warranty

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

TESTING

Performance Test Standards

Product tested to 500 lbs static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.